

### 1. IDENTIFICATION

Product Name Regular BCM Dry Chemical

(Fire Extinguishing Agent Pressurized and Non-

Regular, Stearated B:C, Sodium Bicarbonate, BCM

pressurized)

**Other Names** 

Recommended use of the chemical and

restrictions on use

**Company Identification** 

**Identified uses** Fire Extinguishing Agent

**Restrictions on use**Consult applicable fire protection codes

Kidde-Fenwal, Inc. 400 Main Street Ashland, MA 01721

USA

**Customer Information Number Emergency Telephone Number** 

CHEMTREC Number

(508) 881-2000

(800) 424-9300 (703) 527-3887 (International)

Issue Date October 29, 2019
Supersedes Date October 1, 2015

Safety Data Sheet prepared in accordance with OSHA's Hazard Communication Standard (29 CFR 1910.1200, the Canadian Hazardous Products Regulations (HPR) and the Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

### 2. HAZARD IDENTIFICATION

This SDS covers the product listed above as sold in pressurized and non-pressurized containers. GHS classifications for both forms are listed below.

### **GHS Classification - Pressurized**

### **Hazard Classification**

Gas under pressure - Compressed gas

### **Label Elements**

Hazard Symbols



Signal Word: Warning

### **Hazard Statements**

Contents under pressure; may explode if heated.

Revision Date: October 29, 2019 Page 1 of 9



### 2. HAZARD IDENTIFICATION

**Precautionary Statements** 

**Prevention** 

None

Response

None

**Storage** 

Protect from sunlight.

Store in well-ventilated place.

**Disposal** 

None

GHS Classification: Non - pressurized

### **Hazard Classification**

This product is classified as not hazardous in accordance with the Globally Harmonized System of Classification and Labelling (GHS).

### **Label Elements**

Hazard Symbols

None

Signal Word: None

### **Hazard Statements**

None

### **Precautionary Statements**

Prevention

None

Response

None

Storage

None

**Disposal** 

None

### **Other Hazards**

This product may contain small quantities of quartz (crystalline silica) as an impurity. Prolonged exposure to respirable crystalline silica dust at concentrations exceeding the occupational exposure limits may increase the risk of developing a disabling lung disease known as silicosis. IARC found limited evidence for pulmonary carcinogenicity of crystalline silica in humans.

### **Specific Concentration Limits**

The values listed below represent the percentages of ingredients of unknown toxicity.

Acute oral toxicity <10%
Acute dermal toxicity <10%
Acute inhalation toxicity <10%
Acute aquatic toxicity <10%

Revision Date: October 29, 2019 Page 2 of 9



Non-pressurized)

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

This product is a mixture.

 Component
 CAS Number
 Concentration\*

 Mica
 12001-26-2
 1 - 5%

 Talc
 14807-96-6
 1 - 5%

 Calcium carbonate
 471-34-1
 1 - 5%

Note: Pressurized product uses nitrogen or compressed air as the expellant.

### 4. FIRST- AID MEASURES

### Description of necessary first-aid measures

### Eves

Immediately flood the eye with plenty of water for at least 15 minutes, holding the eye open. Obtain medical attention if soreness or redness persists.

### Skin

Wash skin thoroughly with soap and water. Obtain medical attention if irritation persists.

### Ingestion

Dilute by drinking large quantities of water and obtain medical attention.

### Inhalation

Move victim to fresh air. Obtain medical attention immediately for any breathing difficulty.

### Most important symptoms/effects, acute and delayed

Aside from the information found under Description of necessary first aid measures (above) and Indication of immediate medical attention and special treatment needed, no additional symptoms and effects are anticipated.

### Indication of immediate medical attention and special treatment needed Notes to Physicians

Treat symptomatically.

### 5. FIRE - FIGHTING MEASURES

### Suitable Extinguishing Media

This preparation is used as an extinguishing agent and therefore is not a problem when trying to control a blaze. Use extinguishing agent appropriate to other materials involved. Keep pressurized containers and surroundings cool with water spray as they may rupture or burst in the heat of a fire.

### Specific hazards arising from the chemical

Pressurized containers may explode in heat of fire.

### Special Protective Actions for Fire-Fighters

Wear full protective clothing and self-contained breathing apparatus as appropriate for specific fire conditions.

Revision Date: October 29, 2019 Page 3 of 9

<sup>\*</sup>Exact concentration withheld as trade secret.



### 6. ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

Wear appropriate protective clothing. Prevent skin and eye contact. Remove leaking container to a safe place. Ventilate the area.

### **Environmental Precautions**

Prevent large quantities of the material from entering drains or watercourses.

### Methods and materials for containment and cleaning up

Sweep up or vacuum and transfer into suitable containers for recovery or disposal.

### 7. HANDLING AND STORAGE

### Precautions for safe handling

Wear appropriate protective clothing. Prevent skin and eye contact.

### Conditions for safe storage

Pressurized containers should be properly stored and secured to prevent falling or being knocked over. Do not drag, slide or roll pressurized containers. Do not drop pressurized containers or permit them to strike against each other. Never apply flame or localized heat directly to any part of the pressurized or plastic container. Store pressurized and plastic containers away from high heat sources. Storage area should be:
- cool - dry - well ventilated - under cover - out of direct sunlight

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### **Control parameters**

Exposure limits are listed below, if they exist.

### Mica

ACGIH TLV: 3 mg/m<sup>3</sup> TWA, measured as respirable fraction of the aerosol.

OSHA PEL: 20 mppcf, <1% crystalline silica

**Calcium Carbonate** 

OSHA PEL: 15 mg/m<sup>3</sup> TWA, total dust

5 mg/m<sup>3</sup> TWA, respirable fraction

### Talc, containing no asbestos fibers

ACGIH TLV: 2 mg/m³ TWA, measured as respirable fraction of the aerosol. The value is for particulate matter containing no asbestos and <1% crystalline silica

OSHA PEL: 20,000 mppcf, containing <1% quartz Particulates not otherwise classified /regulated

OSHA PEL: 50 mppcf or 15 mg/m3 TWA, total dust

15 mppcf or 5 mg/m<sup>3</sup> TWA, respirable fraction

### Appropriate engineering controls

Use with adequate ventilation. If this product is used in a pressurized system, there should be local procedures for the selection, training, inspection and maintenance of this equipment. When used in large volumes, use local exhaust ventilation.

### Individual protection measures

### **Respiratory Protection**

Not normally required. Use dust mask where dustiness is prevalent, or TLV is exceeded. In oxygen deficient atmospheres, use a self-contained breathing apparatus, as an air purifying respirator will not provide protection.

Revision Date: October 29, 2019 Page 4 of 9



### SAFETY DATA SHEET

Regular BCM Dry Chemical (Fire Extinguishing Agent - Pressurized and Non-pressurized)

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Skin Protection

Gloves

**Eye/Face Protection** 

Chemical goggles or safety glasses with side shields.

**Body Protection** 

Normal work wear.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

### Agent - Regular BCM Dry Chemical

**Appearance** 

Physical State Solid (powder)

Color White Odorless

Odor Odorless
Odor Threshold No data available

pH Not applicable

Specific Gravity ~2.3

Boiling Range/Point (°C/F)

Melting Point (°C/F)

Flash Point (PMCC) (°C/F)

Vapor Pressure

Evaporation Rate (BuAc=1)

Solubility in Water

Vapor Density (Air = 1)

Not applicable

No data available
No data available
16.4g/100g
Not applicable

VOC (g/l) None VOC (%) None

Partition coefficient (n- No data available

octanol/water)

Viscosity

Auto-ignition Temperature

Decomposition Temperature
Upper explosive limit
Lower explosive limit
Flammability (solid, gas)

No data available
No data available
No data available
No data available

Expellant - Nitrogen

**Appearance** 

Physical State Compressed gas

Color Colorless None

**Odor** None

Odor Threshold No data available PH Not applicable

**Specific Gravity** 0.075 lb/ft³ @70°F as vapor

Boiling Range/Point (°C/F)

Melting Point (°C/F)

Flash Point (PMCC) (°C/F)

Vapor Pressure

Evaporation Rate (BuAc=1)

Solubility in Water

-196°C/-321°F

-210°C/-346°F

Not flammable
No data available
Not applicable

 Solubility in Water
 0.02 g/L

 Vapor Density (Air = 1)
 0.97

 VOC (g/l)
 None

 VOC (%)
 None

Revision Date: October 29, 2019 Page 5 of 9



### SAFETY DATA SHEET

Regular BCM Dry Chemical (Fire Extinguishing Agent - Pressurized and Non-pressurized)

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Partition coefficient (n-

No data available

octanol/water)

Not applicable

Viscosity
Auto-ignition Temperature
Decomposition Temperature
Upper explosive limit
Lower explosive limit
Flammability (solid, gas)

No data available No data available Not explosive Not explosive Not flammable

### 10. STABILITY AND REACTIVITY

### Reactivity

Pressurized containers may rupture or explode if exposed to heat.

### **Chemical Stability**

Stable under normal conditions.

### Possibility of hazardous reactions

Hazardous polymerization will not occur.

### **Conditions to Avoid**

Exposure to direct sunlight - contact with incompatible materials

### **Incompatible Materials**

Strong acids

### **Hazardous Decomposition Products**

Oxides of carbon

### 11. TOXICOLOGICAL INFORMATION

### **Acute Toxicity**

Mica:

Oral LD50 (Rat) >2000 mg/kg

Nitrogen

Simple asphyxiant

### Specific Target Organ Toxicity (STOT) - single exposure

<u>Nitrogen:</u> Exposure to nitrogen gas at high concentrations can cause suffocation by reducing oxygen available for breathing. Breathing very high concentrations can cause dizziness, shortness of breath, unconsciousness or asphyxiation.

### Specific Target Organ Toxicity (STOT) - repeat exposure

No relevant studies identified.

### Serious Eye damage/Irritation

Mica: Not irritating (rabbit)

### Skin Corrosion/Irritation

Mica: Not irritating (rabbit)

Revision Date: October 29, 2019 Page 6 of 9



### 11. TOXICOLOGICAL INFORMATION

### Respiratory or Skin Sensitization

No relevant studies identified.

### Carcinogenicity

This product may contain small quantities of quartz (crystalline silica) as an impurity. Prolonged exposure to respirable crystalline silica dust at concentrations exceeding the occupational exposure limits may increase the risk of developing a disabling lung disease known as silicosis. IARC has classified Silica Dust, Crystalline, in the form of quartz or cristobalite as 1 (carcinogenic to humans).

### **Germ Cell Mutagenicity**

No relevant studies identified.

### **Reproductive Toxicity**

No relevant studies identified.

### **Aspiration Hazard**

Not an aspiration hazard.

### 12. ECOLOGICAL INFORMATION

### **Ecotoxicity**

No relevant studies identified.

### Mobility in soil

No relevant studies identified.

### Persistence/Degradability

No relevant studies identified.

### **Bioaccumulative Potential**

No relevant studies identified.

### Other adverse effects

No relevant studies identified.

### 13. DISPOSAL CONSIDERATIONS

### **Disposal Methods**

Dispose of container in accordance with all applicable local and national regulations.

### 14. TRANSPORT INFORMATION

Safety Data Sheet information is intended to address a specific material and not various forms or states of containment.

### **Pressurized Containers**

DOT CFR 172.101 Data
UN Proper Shipping Name
UN Class

Fire extinguishers, 2.2, UN1044 Fire extinguishers (2.2)

Revision Date: October 29, 2019 Page 7 of 9



### 14. TRANSPORT INFORMATION

UN Number UN1044 UN Packaging Group UN1044 Not applicable

Classification for AIR Consult current IATA Regulations prior to shipping by air.

Transportation (IATA)

Classification for Water Consult current IMDG Regulations prior to shipping by water.

**Transport IMDG** 

Non-pressurized Containers

**DOT CFR 172.101 Data UN Proper Shipping Name**Not Regulated
Not Regulated

UN Class None.
UN Number None.
UN Packaging Group None.
lassification for AIR Consult current IATA Regulations prior to shipping by air.

Classification for AIR Transportation (IATA) Classification for Water

lassification for Water Consult current IMDG Regulations prior to shipping by water.

**Transport IMDG** 

This section is believed to be accurate at the time of preparation. It is not intended to be a complete statement or summary of the applicable laws, rules, or hazardous material regulations, and is subject to change. Users have the responsibility to confirm compliance with all laws, rules, and hazardous material regulations in effect at the time of shipping.

### 15. REGULATORY INFORMATION

### United States TSCA Inventory

This product contains ingredients that are listed on or exempt from listing on the EPA Toxic Substance Control Act Chemical Substance Inventory.

### Canada DSL Inventory

All ingredients in this product are listed on the Domestic Substance List (DSL) or the Non-Domestic Substance List (NDSL) or are exempt from listing.

SARA Title III Sect. 311/312 Categorization: Pressurized

Gas under pressure

SARA Title III Sect. 311/312 Categorization: Non-pressurized

None

### SARA Title III Sect. 313

This product does not contain any chemicals that are listed in Section 313 at or above de minimis concentrations.

### 16. OTHER INFORMATION

### NFPA Ratings

NFPA Code for Health - 1

NFPA Code for Flammability - 0

NFPA Code for Reactivity - 0

NFPA Code for Special Hazards - None

Revision Date: October 29, 2019 Page 8 of 9



### 16. OTHER INFORMATION

Legend

ACGIH: American Conference of Governmental Industrial Hygienists

CAS#: Chemical Abstracts Service Number

EC50: Effect Concentration 50%

IARC: International Agency for Research on Cancer

LC50: Lethal Concentration 50%

LD50: Lethal Dose 50%

N/A: Denotes no applicable information found or available OSHA: Occupational Safety and Health Administration

PEL: Permissible Exposure Limit STEL: Short Term Exposure Limit TLV: Threshold Limit Value

TSCA: Toxic Substance Control Act

Revision Date: October 29, 2019 Replaces: October 1, 2015

Changes made: Updates to sections 1, 3, 8, 9, 11, 12, 15 and 16.

### Information Source and References

This SDS is prepared by Hazard Communication Specialists based on information provided by internal company references.

Prepared By: EnviroNet LLC.

The information and recommendations presented in this SDS are based on sources believed to be accurate. Kidde-Fenwal, Inc. assumes no liability for the accuracy or completeness of this information. It is the user's responsibility to determine the suitability of the material for their particular purposes. In particular, we make NO WARRANTY OF MERCHANTABILITY OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, with respect to such information, and we assume no liability resulting from its use. Users should ensure that any use or disposal of the material is in accordance with applicable Federal, State, and local laws and regulations.

Revision Date: October 29, 2019 Page 9 of 9